



Toll free: 8, , !- - +!+, \* +

Specifications for:

## 18,000 Gallon Open Top Weir Tanks

### Mechanical features:

- 3" top fill tube
- 4 Standard 22" side hinged accessways
- Multiple 4" valved fill/drain ports including floor level valves for low point drain out
- 4" Vent
- Sloped bottom for 100% drain out and easier cleaning after use
- Smooth wall construction - no internal cross bracing
- Front mounted ladderwell for top access
- Fixed rear axle
- Nose rail cut - out for easy access when installing hose and fittings on the front /bottom of tank
- Equipped with internal baffles or weirs (over and under) to accelerate settling of unwanted solids and fine sediments, may also be used in the separation of unwanted floating materials
- This tank can be used in a pump through capacity or in a batch treatment capacity
- Flows of up to 100 GPM are achievable depending on your circumstances. The tank may also be modified to achieve higher flows while keeping efficiency
- Contact your local representative for assistance

### Safety features:

- All tanks are equipped with non-slip step material on ladderwells and catwalks
- All tanks are equipped with folding safety handrails
- All rails and catwalks are painted "safety yellow" for high visibility
- Safe operation reminder decals are applied on risk areas such as steps, valves and hatches
- Tanks are equipped with fill level charts and may be fitted with audible alarms, strobes and level gauges(digital and mechanical)





---

Drawing for:

**18,000 Gallon Open Top Weir Tanks**

