

GP6600A

Portable Generators



**WACKER
NEUSON**
all it takes!



Rugged and powerful premium portable power

Designed for construction, rental and other demanding applications, these quiet, high-performance, portable generators deliver unmatched tool starting and voltage regulation in a rugged compact package. Excellent for powering single or multiple tools on an entire job site or as emergency or standby power. Built with heavy-duty frames and premium components to provide long, trouble-free operation even in abusive environments. Ideal for powering high starting amperage tools such as compressors, grinders, fusion welders as well as all your Wacker Neuson electric power tools.

- Best in class tool starting and voltage regulation due to a unique step-start generator technology with Automatic Voltage Regulation (AVR) and separate excitation winding.
- Central GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures while offering personal protection on all receptacles including 240 Volt. Meets the latest NEC and OSHA jobsite standard
- Unique auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear.
- Robust, powder coated steel frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock-mounting combine to provide outstanding impact protection.
- Proven Honda GX390 engine with low oil shutdown. Fully compliant with the latest EPA evaporative emissions

regulations.

GP6600A Technical specifications

Dimensions

L x W x H	28.0 x 21.6 x 20.3 in
L x W x H - Shipping	28.6 x 22.4 x 21.6 in
Shipping weight	183 lb

Operating data

Operating weight	223 lb
Circuit breaker AC - 1 Phase 2 Pole	27 A
Receptacles	(2) 125V, 20A duplex 5-20R
Receptacles	(1) 125V, 30A twist lock L5-30R
Receptacles	(1) 125/250V, 30A twist lock L14-30R

Electrical system

Electrical power Maximum Output	6,600 W
Electrical power Continuous Output	6,000 W
Voltage AC - 1 Phase	120/240 V
Frequency	60 Hz
Power factor	1 cos Φ 1~
Generator model	AVR with Brushes
Generator insulation (class)	B
Power Rating Specification	SAE J1349

Engine / Motor

Engine / Motor	Honda GX390
Cylinder	1
Displacement	23.7 in ³
Operating performance	11.66 hp
RPM / speed	3,600 rpm
Tank capacity Oil	1.2 US qt
Tank capacity Fuel	5.5 US gal
Fuel type	Gasoline
Fuel consumption	1 US gal/h
Runtime	5.4 h

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2022 Wacker Neuson SE.